

VMVL PVC 90°C

H05V2V2-F

Litze: blanke koper litze volgens VDE klasse 5

Aders: volgens DIN VDE 0293

Mantel: hittebestendig PVC T13 volgens HD 21.1 S3

Nominale spanning: 300/ 500V

Beproevingsspanning: 2kV

Temperatuurbereik: statisch: -40°C tot +90°C
bewegend: +5°C tot +90°C



Aders	mm ²	CU kg/km	Mantel kleur	Artikelnr. 100m ring	Artikelnr. 500m hasp.
2	0,75	14,4	zwart	10605049	10605052
2	0,75	14,4	wit	10605056	10605059
2	1,00	19,0	zwart	10605544	10605547
2	1,00	19,0	wit	10605551	10605554
3	0,75	21,6	zwart	10605148	10605151
3	0,75	21,6	wit	10605155	10605158
3	1,00	29,0	zwart	10605643	10605646
3	1,00	29,0	wit	10605650	10605653
3	1,50	43,0	zwart	10606138	10606141
3	1,50	43,0	wit	10606145	10606148
3	2,50	72,0	zwart	10606633	10606636
3	2,50	72,0	wit	10606640	10606643
4	0,75	29,0	zwart	10605247	10605250
4	0,75	29,0	wit	10605254	10605257
4	1,00	38,0	zwart	10605742	10605745
4	1,00	38,0	wit	10605749	10605752
4	1,50	58,0	zwart	10606237	10606240
4	1,50	58,0	wit	10606244	10606247
4	2,50	96,0	zwart	10606732	10606735
4	2,50	96,0	wit	10606739	10606742
5	0,75	36,0	zwart	10605346	10605349
5	0,75	36,0	wit	10605353	10605356
5	1,00	48,0	zwart	10605841	10605844
5	1,00	48,0	wit	10605848	10605851
5	1,50	72,0	zwart	10606336	10606339
5	1,50	72,0	wit	10606343	10606346
5	2,50	120,0	zwart	10606831	10606834
5	2,50	120,0	wit	10606838	10606841

Andere verpakkingen of grotere haspels op aanvraag.

Voor specificaties, neem contact met ons op!