

LIYY – UL - CSA

Litze: vertinde koper litze

Mantel: SR-PVC grijs

Isolatie weerstand: 0,14mm²: 140Ω/km bij 20°C
 0,23mm²: 92Ω/km bij 20°C
 0,56mm²: 33Ω/km bij 20°C

Nominale spanning: max 300V

Beproevingsspanning: > 1500V

Temperatuurbereik: statisch: -30°C tot +80°C
 bewegend: -10°C tot +50°C



Aders	mm ²	CU kg/km	Artikelnr. 100m ring	Artikelnr. 500m hasp.
4	0,14	5,6	11800048	11800051
6	0,14	8,4	11800147	11800150
2	0,23	4,6	11800246	11800249
4	0,23	9,2	11800345	11800348
8	0,23	19,4	11800444	11800447
10	0,23	23,0	11800543	11800546
2	0,56	11,2	11800642	11800645
3	0,56	16,8	11800741	11800744
4	0,56	22,4	11800840	11800843

LIYCY – UL - CSA

Litze: vertinde koper litze

Mantel: SR-PVC grijs

Isolatie weerstand: 0,14mm²: 140Ω/km bij 20°C
 0,23mm²: 92Ω/km bij 20°C
 0,56mm²: 33Ω/km bij 20°C

Nominale spanning: max 300V

Beproevingsspanning: > 1500V

Temperatuurbereik: statisch: -30°C tot +80°C
 bewegend: -10°C tot +50°C



Aders	mm ²	CU kg/km	Artikelnr. 100m ring	Artikelnr. 500m hasp.
2	0,14	10,7	11900050	11900053
3	0,14	12,1	11900149	11900152
4	0,14	13,5	11900248	11900251
6	0,14	19,0	11900347	11900350
2	0,23	12,5	11900446	11900449
3	0,23	14,7	11900545	11900548
4	0,23	19,6	11900644	11900647
8	0,23	31,2	11900743	11900746
2	0,56	21,7	11900842	11900845
3	0,56	27,3	11900941	11900944
4	0,56	32,9	11901040	11901043
8	0,56	66,3	11901139	11901142

Voor specificaties, neem contact met ons op!