

# Siliconen snoer/kabel

## SIF - SIHF

**Litze:** fijndradige vertinde litze volgens VDE 0295 klasse 5

**Mantel:** siliconen

**Nominale spanning:** 300V/500V

**Beproevingsspanning:** 2kV

**Temperatuurbereik:** -60°C tot +180°C kortstondig + 250°C



### SIF

| mm <sup>2</sup> | vpe* (mtr) | CU<br>kg/km | Artikelnr.<br>Zwart | Artikelnr.<br>Blauw | Artikelnr.<br>Bruin | Artikelnr.<br>Wit | Artikelnr.<br>Geel/groen |
|-----------------|------------|-------------|---------------------|---------------------|---------------------|-------------------|--------------------------|
| 0,50            | 100        | 4,8         | 11000101            | 11000103            | 11000108            | 11000107          | 11000112                 |
| 0,75            | 100        | 7,2         | 11000301            | 11000303            | 11000308            | 11000307          | 11000312                 |
| 1,00            | 100        | 9,6         | 11000501            | 11000503            | 11000508            | 11000507          | 11000512                 |
| 1,50            | 100        | 14,4        | 11000701            | 11000703            | 11000708            | 11000707          | 11000712                 |
| 2,50            | 100        | 24,0        | 11000901            | 11000903            | 11000908            | 11000907          | 11000912                 |
| 4,00            | 100        | 38,0        | 11001101            | 11001103            | 11001108            | 11001107          | 11001112                 |
| 6,00            | 100        | 58,0        | 11001301            | 11001303            | 11001308            | 11001307          | 11001312                 |

Andere kleuren op aanvraag

### SIHF

| Aders | mm <sup>2</sup> | CU<br>kg/km | Mantel<br>kleur | Artikelnr.<br>ring |
|-------|-----------------|-------------|-----------------|--------------------|
| 2     | 0,75            | 14,4        | rd/bn           | 11100942           |
| 2     | 1,00            | 19,0        | rd/bn           | 11101833           |
| 2     | 1,50            | 29,0        | rd/bn           | 11102823           |
| 2     | 2,50            | 48,0        | rd/bn           | 11103714           |
| 3     | 0,75            | 21,6        | rd/bn           | 11101041           |
| 3     | 1,00            | 29,0        | rd/bn           | 11101932           |
| 3     | 1,50            | 43,0        | rd/bn           | 11102922           |
| 3     | 2,50            | 72,0        | rd/bn           | 11103813           |
| 4     | 0,75            | 29,0        | rd/bn           | 11101140           |
| 4     | 1,00            | 38,0        | rd/bn           | 11102031           |
| 4     | 1,50            | 58,0        | rd/bn           | 11103021           |
| 4     | 2,50            | 96,0        | rd/bn           | 11103912           |
| 5     | 0,75            | 36,0        | rd/bn           | 11101239           |
| 5     | 1,00            | 48,0        | rd/bn           | 11102130           |
| 5     | 1,50            | 72,0        | rd/bn           | 11103120           |
| 5     | 2,50            | 120,0       | rd/bn           | 11104011           |

Andere kwadraturen of aderaantallen op aanvraag leverbaar.

vpe, standaard op ringen van 100 meter. Ook leverbaar op haspels.

**Voor specificaties, neem contact met ons op!**